

Bid Number: GEM/2019/B/154008 Dated: 09-01-2019

Bid Document		
Bid Details		
Bid End Date/Time	24-01-2019 09:00:00	
Bid Life Cycle (From Publish Date)	90 (Days)	
Bid Offer Validity (From End Date)	15 (Days)	
Ministry/State Name	Ministry Of Home Affairs	
Department Name	Central Armed Police Forces	
Organisation Name	Border Security Force (bsf)	
Office Name	North Bengal	
Total Quantity	10	
Item Category	revolving chair , revolving chair	
MSE Exemption For Years Of Experience And Turnover	Yes	

Revolving Chair (5)

Technical Specifications

* As per GeM Category Specification

Specification	Specification Name	Values	Allowed Values
GENERAL	Chair Type	360 Degree swivel,posture control with multilocking position synchronized mechanism	*
	Tilt Tension Adjustment	No	*
	Height Adjustment ± 5(mm)	N.A	up to 100 mm, up to 120 mm, N.A, up to 90 mm, up to 65 mm
	Arm	With	With, Without
	Type of backrest support	Backrest With Adjustable Lumber Support	backrest with lumber support of polypropylene at multilevel across back, backrest symmetrical lumber support, Backrest With

			Adjustable Lumber Support
	Arm Type	Fixed	Adjustable, Fixed, NA
	Colour of Fabric for Seat and Backrest	brown	*
	Ergonomic Seat Design	No	Yes, No
	Back type	push back	push back, fixed, height adjustable
	Backrest is made of two pcs injection moulded frame	Backrest is made of one piece injection moulded frame	*
	backrest has separate adjustable headrest	No	Yes, No
	Seat type	fixed	fixed, sliding
	Seat is curved	Yes	*
	Locking mechanism	No	*
	Type of locking	N.A	*
	Number of arm movement	N.A	2(up & down), 4(up & down end left & right), 6(Up & Down,Left & Right And Swivel), 8(Up & Down,Left & Right,Swivel And Front & Back), N.A
	Lumber support	N.A	integrated, external & fixed, external & adjustable, N.A
MATERIAL	Pedestal Base	Stainless Steel with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size	Glass Fibre Nylon with ABS/ NylonTwin Caster Wheels Minimum 5 Nos, of 50 mm Size, ABS Plasstic with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Electro Coated with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Stainless Steel with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Aluminium Die Cast with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Aluminium

		Die Cast Chrome Finish With Nylon Twin Caster Wheels Minimum Of 50-70 Mm Diameter, , Nylon Base With Nylon Twin Caster Wheels Minimum Of 50-70 Mm Diameter, Aluminium Alloy With Nylon Twin Caster Wheels Minimum Of 50-70 Diameter, Wooden Cladded With Nylon Twin Caster Wheels Minimum Of 50-70 Mm Diameter, Chrome finish with 5 wheels
Arm Material	steel covered with polyurethane	steel covered with polyurethane, pu foam bonded chrome coted, aluminium covered with pu, CRCA pipe with foam, 19 mm (+/- 2 mm) ROUND pipe with cushion, 19 mm (+/- 2 mm) round SS pipe with cushion, Proypylene, Steel covered with polypropelene, Steel Covered with Wooden Cladding, WITHOUT ARM
seat material	PU Foam Covered With pure leatherite	pressed and moulded plywood with polypropylene cover, PU foam covered with mesh fabric, PU Foam covered with Fabric, PU Foam Covered With pure leather, PU Foam Covered With pure leatherite
Density of PU foam used in seat KG per Cu Meter (+/- 3)	35	*
Density of PU foam used in backrest in KG per Cu Meter (+/- 3)	35	*
Material of Fabric Back Cover	N.A	mesh fabric, Innner frame Upholstered with Mesh fabric and mounted on main assembly, pure leather, 100% polyester fabric,

			nylon with poly olefin elastomer, Leatherite, N.A
	Material of Fabric of Seat Cover	N.A	foam laminated mesh fabrics, Mesh Fabrics, pure leather, leatherite, 100% polyester fabric, N.A
	GSM/Thickness of fabric ±5%(Gram/Square meter)	N.A	*
DIMENSION	Overall Chair Height ±15mm	670	*
	Backrest Height ±15mm	460	*
	Backrest Width ±10mm	410	*
	Seat Height ±15 mm	420	420, 450, 480, 500, 520
	Seat Width ±10 mm	440	440, 480, 500, 520, 550, 460, 360
	Seat Depth ±10 mm	400	400, 460, 480, 500, 520, 550, 420, 440, 540, 360
	Thickness of M S Plate Joining the under structure with Seat	0.2	*
	Thickness of Plywood used in Seat ±1(mm)	N.A	12 mm, 15 mm, 18 mm, N.A
	Thickness of Plywood used in Backrest ± 1(mm)	N.A	12 mm, 15 mm, 18 mm, N.A
	Padestal Size (Diameter in mm) +/- 10 mm	600	*
	Thickness of Polyurethane Foam Used in Seat in mm (+/- 2 mm)	N.A	*
	Thickness of Polyurethane Foam Used in Backrest IN MM (+/- 2 MM)	N.A	*
WARANTEE	Warrantee period in number of years	1-year	1-year, 2-year, 3-year, 4-year, 5-year
CERTIFICATION	Test reports to be furnished to buyer	YES	YES, NO

on demand		
BIFMA Certification	NO	YES, NO
OEM of offered product is ISO 9001:2015 certified	NO	YES, NO
OEM of offered product is ISO 14001:2015 certified	NO	YES, NO
OEM of offered product is ISO 18001:2007 certified	NO	YES, NO
Green guard certification	NO	YES, NO
Aiota	-	YES, NO

* Bold specifications are the golden parameters.

Consignees/Reporting Officer and Quantity

S.No.	Consignee/Reporti ng Officer	Address	Quantity	Delivery Days
1	PADAM BORO	734011,CH BSF, KADAMTALA	5	15

Revolving Chair (5)

Technical Specifications

* As per GeM Category Specification

Specification	Specification Name	Values	Allowed Values
GENERAL	Chair Type	360 Degree swivel,posture control with multilocking position synchronized mechanism	*
	Tilt Tension Adjustment	No	*
	Height Adjustment ± 5(mm)	up to 100 mm	up to 100 mm, up to 120 mm, N.A, up to 90 mm, up to 65 mm
	Arm	With	With, Without
	Type of backrest support	backrest symmetrical lumber support	backrest with lumber support of polypropylene at multilevel across back, backrest symmetrical lumber support,

			Backrest With Adjustable Lumber Support
	Arm Type	Fixed	Adjustable, Fixed, NA
	Colour of Fabric for Seat and Backrest	black	*
	Ergonomic Seat Design	Yes	Yes, No
	Back type	push back	push back, fixed, height adjustable
	Backrest is made of two pcs injection moulded frame	Backrest is made of two pcs injection moulded frame	*
	backrest has separate adjustable headrest	No	Yes, No
	Seat type	fixed	fixed, sliding
	Seat is curved	Yes	*
	Locking mechanism	No	*
	Type of locking	N.A	*
	Number of arm movement	N.A	2(up & down), 4(up & down end left & right), 6(Up & Down,Left & Right And Swivel), 8(Up & Down,Left & Right,Swivel And Front & Back), N.A
	Lumber support	N.A	integrated, external & fixed, external & adjustable, N.A
MATERIAL	Pedestal Base	ABS Plasstic with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size	Glass Fibre Nylon with ABS/ NylonTwin Caster Wheels Minimum 5 Nos, of 50 mm Size, ABS Plasstic with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Electro Coated with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Stainless Steel with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50 mm Size, Aluminium Die Cast with ABS/Nylon Twin Caster Wheels Minimum 5 Nos, of 50

		mm Size, Aluminium Die Cast Chrome Finish With Nylon Twin Caster Wheels Minimum Of 50-70 Mm Diameter, , Nylon Base With Nylon Twin Caster Wheels Minimum Of 50-70 Mm Diameter, Aluminium Alloy With Nylon Twin Caster Wheels Minimum Of 50-70 Diameter, Wooden Cladded With Nylon Twin Caster Wheels Minimum Of 50-70 Mm Diameter, Chrome finish with 5 wheels
Arm Material	Proypylene	steel covered with polyurethane, pu foam bonded chrome coted, aluminium covered with pu, CRCA pipe with foam, 19 mm (+/- 2 mm) ROUND pipe with cushion, 19 mm (+/- 2 mm) round SS pipe with cushion, Proypylene, Steel covered with polypropelene, Steel Covered with Wooden Cladding, WITHOUT ARM
seat material	PU foam covered with mesh fabric	pressed and moulded plywood with polypropylene cover, PU foam covered with mesh fabric, PU Foam covered with Fabric, PU Foam Covered With pure leather, PU Foam Covered With pure leatherite
Density of PU foam used in seat KG per Cu Meter (+/- 3)	35	*
Density of PU foam used in backrest in KG per Cu Meter (+/- 3)	35	*
Material of Fabric Back Cover	N.A	mesh fabric, Innner frame Upholstered with Mesh fabric and mounted on main assembly, pure leather,

			100% polyester fabric, nylon with poly olefin elastomer, Leatherite, N.A
	Material of Fabric of Seat Cover	N.A	foam laminated mesh fabrics, Mesh Fabrics, pure leather, leatherite, 100% polyester fabric, N.A
	GSM/Thickness of fabric ±5%(Gram/Square meter)	N.A	*
DIMENSION	Overall Chair Height ±15mm	670	*
	Backrest Height ±15mm	460	*
	Backrest Width ±10mm	410	*
	Seat Height ±15 mm	420	420, 450, 480, 500, 520
	Seat Width ±10 mm	440	440, 480, 500, 520, 550, 460, 360
	Seat Depth ±10 mm	400	400, 460, 480, 500, 520, 550, 420, 440, 540, 360
	Thickness of M S Plate Joining the under structure with Seat	0.2	*
	Thickness of Plywood used in Seat ±1(mm)	N.A	12 mm, 15 mm, 18 mm, N.A
	Thickness of Plywood used in Backrest ± 1(mm)	N.A	12 mm, 15 mm, 18 mm, N.A
	Padestal Size (Diameter in mm) +/- 10 mm	600	*
	Thickness of Polyurethane Foam Used in Seat in mm (+/- 2 mm)	N.A	*
	Thickness of Polyurethane Foam Used in Backrest IN MM (+/- 2 MM)	N.A	*
WARANTEE	Warrantee period in number of years	1-year	1-year, 2-year, 3-year, 4-year, 5-year
CERTIFICATION	Test reports to be	NO	YES, NO

furnished to buyer on demand		
BIFMA Certification	NO	YES, NO
OEM of offered product is ISO 9001:2015 certified	NO	YES, NO
OEM of offered product is ISO 14001:2015 certified	NO	YES, NO
OEM of offered product is ISO 18001:2007 certified	NO	YES, NO
Green guard certification	NO	YES, NO
Aiota	-	YES, NO

* Bold specifications are the golden parameters.

Consignees/Reporting Officer and Quantity

S.No.	Consignee/Reporti ng Officer	Address	Quantity	Delivery Days
1	Brajesh Kumar	734011,CH BSF, KADAMTALA	5	15

EMD Detail

Requ	· · · · ·
I DOALL	Iroa
neuu	neu

ePBG Detail

Required

No

No

Splitting

Bid splitting not applied.

Buyer Specific Additional Terms and Conditions

1. Scope of supply (Bid price to include all cost components) : Only supply of Goods

- 2. **Procurement under this bid is reserved for purchase from :** Local Supplier as defined in Public Procurement (Preference to Make in India), Order 2017 and its subsequent Orders / Notifications issued by concerned Nodal Ministry for specific Goods/ Products.
- 3. The Purchaser reserves the right to increase or decrease the ordered quantity up to 25 percent at the time of placement of contract . The purchaser also reserves the right to increase the contracted qty up to 25% during the currency of the contract at the contracted rates. Bidders are bound to accept the orders accordingly

This Bid is also governed by the General Terms and Conditions

---Thank You---